

Hyper A+ Server AS -1125HS-TNR

1U Hyper with 8 hot-swap 2.5" NVMe/SAS/SATA bays and 3 PCIe 5.0 x16 slots



[More details here](#)

Key Applications

Virtualization, Software-defined Storage, AI Inference and Machine Learning, Cloud Computing, Enterprise Server,

Key Features

- Dual AMD EPYC™ 9004/9005* Series Processors
(*AMD EPYC™ 9005 series drop-in support requires board revision 2.xx);
- Support up to DDR5 24 DIMM slots (1DPC), speed up to 6400MT/s
(Please check System Memory Section for detail);
- 2 PCIe 5.0 x16 FHFL slots
1 PCIe 5.0 x16 FHHL slot
Flexible networking options with 1 AIOM networking slot (OCP NIC 3.0 compatible);
- 8 Hot-swap 2.5" NVMe/SATA/SAS drive bays
Optional 4 Hot-swap 2.5" NVMe/SAS/SATA drive support via additional parts
2 M.2 PCIe 3.0 NVMe slots;
- Dual 1200W Redundant Titanium Level power supplies
(Power supply full redundancy based on configuration and application load);



Form Factor	1U Enclosure: 437 x 43 x 747mm (17.2" x 1.7" x 29.4") Package: 605 x 206 x 1032mm (23.8" x 8.1" x 40.6")
Processor	Dual processor(s) AMD EPYC™ 9004/9005 Series Processors (* AMD EPYC™ 9005 Series drop-in support requires board revision 2.x) Up to 320C/640T
System Memory	Slot Count: 24 DIMM slots Max Memory (1DPC): Up to 6TB 4800MT/s ECC DDR5 RDIMM (AMD EPYC™ 9004 Series Processor, MB R1.x/R2.0/R2.01) Max Memory (1DPC): Up to 6TB 6000MT/s ECC DDR5 RDIMM (AMD EPYC™ 9005 Series Processor, MB R2.0) Max Memory (1DPC): Up to 6TB 6400MT/s ECC DDR5 RDIMM (AMD EPYC™ 9005 Series Processor, MB R2.01)
Drive Bays Configuration	Default: Total 8 bays • 8 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays Option A: Total 12 bays • 12 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bays (*NVMe/SAS/SATA support may require additional storage controller and/or cables, please see the optional parts list for details) M.2: 2 M.2 PCIe 3.0 x4 NVMe slots (M-key 2280/22110)
Expansion Slots	Default • 1 PCIe 5.0 x16 FHHL slot • 2 PCIe 5.0 x16 FHFL slots • 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible)
On-Board Devices	Chipset: System on Chip Network Connectivity: Via AIOM
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port USB: 2 USB 3.0 ports(rear) 1 USB 3.0 port(front) Video: 1 VGA port


(Front View – System)



Drive Bay	Description
1-8	8 Hot-swap 2.5" NVMe/SAS/SATA Drive Bays
9-12	4 Hot-swap 2.5" SAS/SATA Drive Bays ¹ (optional)

¹ NVMe/SAS/SATA functionality depends on configuration chosen and may require additional parts from the optional parts list.
² Drive bays and backplane optional for drive bays 9-11, see optional parts list.

(Rear View – System)



Slot	Slot Description
1	PCIe 5.0 x16 FH (8.5L)
2	PCIe 5.0 x16 FH (10.5L)
3	PCIe 5.0 x16 FH (10.5L)
4	PCIe 5.0 x16 AOM (OCP 3.0)

CPU1 CPU2

*Full redundancy based on configuration and application load

System Cooling	Fans: Up to 8 counter-rotating 40x40x56mm Fan(s) Air Shroud: 2 Air Shrouds
Power Supply	2x 1200W Redundant (1 + 1) Titanium Level (96%) power supplies
System BIOS	BIOS Type: AMI 32MB SPI Flash EEPROM BIOS Features: ACPI 6.4 - Plug and Play (PnP) - SMBIOS 3.5 or later - UEFI 2.8 - USB Keyboard support
Management	SuperCloud Composer®; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); OOB Management Package (SFT-OOB-LIC); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	FAN: Fans with tachometer monitoring - Pulse Width Modulated (PWM) fan connectors - Status monitor for speed control Temperature: Monitoring for CPU and chassis environment - Thermal Control for fan connectors Voltage: System temperature, Memory temperature, CPU temperature, 3.3V standby, +5V standby, +5V, +3.3V, +12V, CPU thermal trip support
Dimensions and Weight	Weight: Gross Weight: 51 lbs (23.1 kg) Net Weight: 32 lbs (14.5 kg) Available Color: Black front & silver body
Operating Environment	Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	Super H13DSH
Chassis	CSE-HS119-R1K24P2-A