



More details here

BigTwin SuperServer SYS-221BT-HNTR

2U 4-Node BigTwin with 6 hot-swap 2.5" NVMe/SATA drives per node

Key Applications

All-Flash NVMe Hyperconverged Infrastructure, Container-as-a-Service;
Application Accelerator, High-Performance File System, Diskless HPC Clusters,

Key Features

- Four **hot-pluggable** systems (nodes) in a 2U form factor. Each node supports the following;;
- Socket E (LGA 4677) support 5th/4th Gen Intel® Xeon® Scalable processors;
- Intel® C741;
- 16 DIMM Slots supporting up to 4TB of memory; ECC RDIMMs up to DDR5-5600;
- 2 PCIe 5.0 x16 (LP) slot; Tool-less support
Internal PCIe 4.0 for 2 x4 M.2 NVMe support onboard
Optional M.2 (22x80) HW RAID1 NVMe Boot Controller via SCC-A2NM2241G3-B1;
- Network connectivity via AIOM (OCP 3.0 compliant);
- 6 hot-swap 2.5" drive bays (2x PCIe 5.0 NVMe/SATA and 4x PCIe 4.0 NVMe/SATA);
- Liquid Cooling Support
4 cooling fans per 2U enclosure, 16K RPM; Shared Cooling Design, Counter-Rotating;



Form Factor: 2U Rack Mount
 3+1+1+1 Redundant Power Supplies (Maximum Level (96%+); Shared Power
 Design;
 Enclosure: 449 x 88 x 730mm (17.68" x 3.47" x 28.75")
 Package: 626 x 248 x 1150mm (24.65" x 9.76" x 45.28")

Processor
 Dual Socket E (LGA-4677)
 5th Gen Intel® Xeon® / 4th Gen Intel® Xeon® Scalable processors
 Supports Intel Xeon CPU Max Series with high bandwidth memory (HBM)
 Up to 64C/128T; Up to 320MB Cache per CPU



System Memory
 Slot Count: 16 DIMM slots
 Max Memory (1DPC): Up to 4TB 5600MT/s ECC DDR5 RDIMM

Drive Bays Configuration
 Default: Total 6 bays
 • 2 front hot-swap 2.5" PCIe 5.0 NVMe/SATA drive bays
 • 4 front hot-swap 2.5" PCIe 4.0 NVMe/SATA drive bays
 M.2: 2 M.2 PCIe 4.0 x4 NVMe slots (M-key 22110(default); VROC required for RAID)

Expansion Slots
 Default
 • 2 PCIe 5.0 x16 LP slots
 • 1 PCIe 5.0 x16 AIOM slot (OCP 3.0 compatible)

On-Board Devices
 Chipset: Intel® C741
 Network Connectivity: Via AIOM

Input / Output
 LAN: 1 RJ45 1 GbE Dedicated BMC LAN port
 USB: 2 USB 3.0 Gen2 Type-A ports(Rear)
 Video: 1 VGA port



System Cooling	Fans: Up to 4x 16K RPM Counter Rotating 8cm Fan(s) Air Shroud: 4 Air Shrouds Liquid Cooling: Direct to Chip (D2C) Cold Plate (optional)
Power Supply	2x 3000W Redundant (1 + 1) Titanium Level (96%) power supplies
System BIOS	BIOS Type: AMI 32MB Flash ROM
Management	SuperCloud Composer®; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!
PC Health Monitoring	CPU: 8+4 Phase-switching voltage regulator Monitors for CPU Cores, Chipset Voltages, Memory. FAN: Fans with tachometer monitoring Pulse Width Modulated (PWM) fan connectors Status monitor for speed control Temperature: Monitoring for CPU and chassis environment
Dimensions and Weight	Weight: Gross Weight: 96.6 lbs (43.8 kg) Net Weight: 66.1 lbs (30 kg) Available Color: Black front & silver body
Operating Environment	RoHS Compliant Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -30°C to 60°C (-22°F to 140°F) Operating Relative Humidity: 8% to 80% (non-condensing) Non-operating Relative Humidity: 8% to 90% (non-condensing)
Motherboard	Super X13DET-B
Chassis	CSE-217BQ2-R3K04P