

W43L100-MRA2FP

43" 4K UHD Marine Display



KEY FEATURES

- 43" 3840 x 2160 resolution with projective capacitive multi-touch screen
- Fanless cooling system
- OSD Key For quick mode changing between ECDIS DAY, DUSK, and NIGHT mode
- 9~36 V DC to DC power input acceptable (Isolation Resistance)
- Meet the requirements of industrial marine standards, compatible with IEC60945 4th Edition, DNVGLCG0339, IACS E10
- Color calibrated for ECDIS compliance (Optional)

INTRODUCTION

The Winmate 4K Marine Display Series comes in sizes from 27" to 55". It offers a clear 3840 x 2160 resolution, and the projective capacitive multi-touch screen enables precise navigation and control. These displays feature narrow bezels and a fanless cooling system for a sleek look and efficient thermal performance. Certified with IEC60945 4th, IACS E10, and DNV-CG-0339, ensuring durability and reliability in maritime environments. With OSD keys for quick switching between ECDIS DAY, DUSK, and NIGHT modes, along with optional color calibration for ECDIS compliance, the series performs well in demanding marine settings. Its wide 9 to 36 V DC input range further enhances suitability for navigation and control applications.

SPECIFICATIONS

Display

Resolution	3840x2160	Size	42.5 inches
Contrast Ratio	4000:1	Panel Brightness	500.0 nits
Display Color	1.07B Colors	View Angles	89,89,89,89
Active Area	941.184x529.416 mm	Touch / Glass	Projected Capacitive Multi Touch Screen (AR Coating) AG film (Optional) AR Glass (Optional)

Environment

Operating Humidity	5% to 95%	Operating Temperature	-15~55°C
Shock	15G,11ms duration	Vibration	0.7g@DNV-CG-0339 (Class A)
IP rating	IP66 (Front Side)	TEMPEST	ignore

Certification


Certification	CE, FCC DNV-CG-0339, IEC60945 4th, IACS E10
---------------	--

IO Ports

USB Port	1 x USB for Touch Screen	Serial Port	1 x RS232 for remote control
Video	1 x VGA 1 x DVI-D 2 x HDMI 2.0	Buzzer	75 dB~80 dB, 2300 Hz, 1m

1 x DP			
Mechanical			
Dimension	1028.8 x 617 x 48 mm	Weight	29.5 kg
Mounting	VESA mount	Enclosure	Metal Housing with Aluminum Bezel
Cooling System	Fanless Design		
Power			
Power Rating	24V DC-in with Isolation (Approval by Certificate) 9~36V DC Input Acceptable	Consumption	100W (Typical)
Accessory			
Accessory	User Manual AC to DC Adapter Power Cord 3 Pin Terminal Block 1 x VGA cable 1 x DVI cable 1 x DP cable 2 x HDMI cable 1 x RS232 cable 1 x USB cable		

DIMENSIONS UNIT:MM



NOTE

1.This is a simplified drawing and some components are not marked in detail.
2.Please contact our sales representative if you need further product information.
3.All specifications are subject to change without prior notice.
4.The product shown in this datasheet is a standard model.For diagrams that contain customized or optional I/ O, please contact the Winmate Sales Team for more information.